



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
1/15

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Product name: Difluoromethane (R32)

Trade name: R32

Other Name: HFC-32

**Additional identification**

Chemical name: Difluoromethane

Chemical formula: CH<sub>2</sub>F<sub>2</sub>

INDEX No. -

CAS-No. 75-10-5

EC No. 200-839-4

REACH Registration No. 01-2119471312-47

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses: Industrial and professional. Perform risk assessment prior to use.  
Refrigerant.  
Use as an Intermediate (transported, on-site isolated).  
Use for electronic component manufacture.  
Using gas alone or in mixtures for the calibration of analysis equipment.  
Formulation of mixtures with gas in pressure receptacles.

Uses advised against Consumer use.

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

Oy Linde Gas Ab  
Itsehallintokuja 6  
FIN-02600 ESPOO Finland

**Telephone:** +358 10 2421

**E-mail:** sds.ren@linde.com

**1.4 Emergency telephone number:** Poison Information Center: open 24 hours a day, tel. 09 471 977



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
2/15

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 as amended.

**Physical Hazards**

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

**2.2 Label Elements**



**Signal Words:** Danger

**Hazard Statement(s):** H220: Extremely flammable gas.  
H280: Contains gas under pressure; may explode if heated.

**Precautionary Statements**

<b>Prevention:</b>	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>Response:</b>	P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381: In case of leakage, eliminate all ignition sources.
<b>Storage:</b>	P403: Store in a well-ventilated place.
<b>Disposal:</b>	None.

**Supplemental label information**

EIGA-0783: Contains fluorinated greenhouse gases

**2.3 Other hazards:** Contact with evaporating liquid may cause frostbite or freezing of skin.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
3/15

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

Chemical name	Difluoromethane
INDEX No.:	-
CAS-No.:	75-10-5
EC No.:	200-839-4
REACH Registration No.:	01-2119471312-47
Purity:	100%
	The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	R32

**SECTION 4: First aid measures**

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

<b>Inhalation:</b>	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
<b>Eye contact:</b>	Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
<b>Skin Contact:</b>	Contact with evaporating liquid may cause frostbite or freezing of skin. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Get medical attention.
<b>Ingestion:</b>	Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Hazards:** Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
4/15

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**SECTION 5: Firefighting measures**

**General Fire Hazards:** Heat may cause the containers to explode.

**5.1 Extinguishing media**

**Suitable extinguishing media:** Water Spray or Fog. Dry powder. Foam.

**Unsuitable extinguishing media:** Carbon Dioxide.

**5.2 Special hazards arising from the substance or mixture:** No data available.

**Hazardous Combustion Products:** If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Hydrogen fluoride  
; Carbon monoxide  
; Carbonyl difluoride

**5.3 Advice for firefighters**

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
5/15

- 6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so.
- 6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation. Eliminate sources of ignition.
- 6.4 Reference to other sections:** Refer to sections 8 and 13.

**SECTION 7: Handling and storage:**

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**SAFETY DATA SHEET**  
**Difluoromethane (R32)**Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
6/15**7.2 Conditions for safe storage,  
including any incompatibilities:**

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):**

None.

**SECTION 8: Exposure controls/personal protection****8.1 Control Parameters****Occupational Exposure Limits**

None of the components have assigned exposure limits.

**DNEL-Values**

Critical component	Type	Value	Remarks
Difluoromethane	Workers - Inhalation, Systemic, long-term	7035 mg/m <sup>3</sup>	Repeated dose toxicity

**PNEC-Values**

Critical component	Type	Value	Remarks
Difluoromethane	Aquatic (freshwater)	0,142 mg/l	-
	Sediment (freshwater)	0,534 mg/kg	-

**8.2 Exposure controls****Appropriate engineering  
controls:**

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.



## SAFETY DATA SHEET Difluoromethane (R32)

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
7/15

### Individual protection measures, such as personal protective equipment

<b>General information:</b>	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.
<b>Eye/face protection:</b>	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
<b>Skin protection</b>	
<b>Hand Protection:</b>	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks.
<b>Body protection:</b>	Wear fire resistant or flame retardant clothing. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.
<b>Other:</b>	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
<b>Respiratory Protection:</b>	Not required.
<b>Thermal hazards:</b>	No precautionary measures are necessary.
<b>Hygiene measures:</b>	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
<b>Environmental exposure controls:</b>	For waste disposal, see section 13 of the SDS.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.





**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
8/15

pH:	Not applicable.
Melting Point:	-136 °C Experimental result, Supporting study
Boiling Point:	-51,6 °C (1.013 hPa) Experimental result, Supporting study
Sublimation Point:	Not applicable.
Critical Temp. (°C):	78,5 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable Gas
Flammability Limit - Upper (%):	33,4 %(V) Experimental result, Supporting study
Flammability Limit - Lower (%):	14 %(V)
Vapor pressure:	No reliable data available.
Vapor density (air=1):	1,8
Relative density:	1,1 (Reference material: Water)
Solubility(ies)	
Solubility in Water:	280 g/l
Partition coefficient (n-octanol/water):	0,2
Autoignition Temperature:	530 °C Experimental result, Key study
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight: 52 g/mol (CH<sub>2</sub>F<sub>2</sub>)

**SECTION 10: Stability and reactivity**

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidizers. For material compatibility see latest version of ISO-11114.





**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
9/15

**10.6 Hazardous Decomposition Products:**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information**

**General information:** May produce irregular heart beat and nervous symptoms.

**11.1 Information on toxicological effects**

**Acute toxicity - Oral Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation Product**

Based on available data, the classification criteria are not met.

**Repeated dose toxicity Difluoromethane**

NOAEL (Rat(Female, Male), Inhalation, 28 d): 49.500 ppm(m) Inhalation  
Experimental result, Supporting study

**Skin Corrosion/Irritation Product**

Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation Product**

Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization Product**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity Product**

Based on available data, the classification criteria are not met.

**Carcinogenicity Product**

Based on available data, the classification criteria are not met.

**Reproductive toxicity Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure Product**

Based on available data, the classification criteria are not met.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
10/15

**Aspiration Hazard  
Product**

Not applicable to gases and gas mixtures..

**Other Relevant Toxicity Information**

Difluoromethane

Cardiac sensitisation threshold limit  
>350000 ppm  
Beagle (dog)LOAEC

Cardiac sensitisation threshold limit  
350000 ppm  
Beagle (dog)NOAEC

Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Acute toxicity  
Product**

No ecological damage caused by this product.

**Acute toxicity - Fish**

Difluoromethane

LC 50 (Pimephales promelas, 96 h): 1.405 mg/l Remarks: QSAR QSAR, Supporting study

**Acute toxicity - Aquatic Invertebrates**

Difluoromethane

EC 50 (Daphnia magna, 48 h): 1.573 mg/l Remarks: QSAR QSAR, Supporting study

**Toxicity to Aquatic Plants**

Difluoromethane

EC 50 (Alga, 96 h): 142 mg/l

**12.2 Persistence and Degradability  
Product**

Not applicable to gases and gas mixtures..

**Biodegradation**

Difluoromethane

5 % (28 d) Detected in water. Experimental result, Key study



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
11/15

**12.3 Bioaccumulative potential**  
**Product**

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil**  
**Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB**  
**assessment**  
**Product**

Not classified as PBT or vPvB.

**12.6 Other adverse effects:**

**Global Warming Potential**

Global warming potential: 675

Contains fluorinated greenhouse gases When discharged in large quantities may contribute to the greenhouse effect. For GWP value of mixture and quantities, refer to container label.

Difluoromethane

EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs

- Global warming potential: 675 Annex 1: Fluorinated greenhouse gases referred to in Point 1 of Article 2; Section 1:Hydrofluorocarbons (HFCs) and its mixtures

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**General information:**

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

**Disposal methods:**

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

**European Waste Codes**

**Container:**

14 06 01\*: chlorofluorocarbons, HCFC, HFC



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
12/15

**SECTION 14: Transport information**

**ADR**

14.1 UN Number:	UN 3252
14.2 UN Proper Shipping Name:	DIFLUOROMETHANE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	23
Tunnel restriction code:	(B/D)
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

**RID**

14.1 UN Number:	UN 3252
14.2 UN Proper Shipping Name	DIFLUOROMETHANE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

**IMDG**

14.1 UN Number:	UN 3252
14.2 UN Proper Shipping Name:	DIFLUOROMETHANE
14.3 Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
EmS No.:	F-D, S-U
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

**SAFETY DATA SHEET**  
**Difluoromethane (R32)**Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
13/15**IATA**

14.1 UN Number: UN 3252  
14.2 Proper Shipping Name: Refrigerant gas R 32  
14.3 Transport Hazard Class(es):  
Class: 2.1  
Label(s): 2.1  
14.4 Packing Group: –  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: –  
Other information  
Passenger and cargo aircraft: Forbidden.  
Cargo aircraft only: Allowed.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Classification	Lower-tier Requirements	Upper-tier Requirements
P2. Flammable gas	10 t	50 t

**National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.  
This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

**15.2 Chemical safety assessment:** CSA has been carried out.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
14/15

**SECTION 16: Other information**

**Revision Information:** Not relevant.

**Key literature references and sources for data:**

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:  
Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).  
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.  
European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>  
European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.  
International Programme on Chemical Safety (<http://www.inchem.org/>)  
ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.  
Matheson Gas Data Book, 7th Edition.  
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.  
The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).  
The European Chemical Industry Council (CEFIC) ERICards.  
United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)  
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).  
Substance specific information from suppliers.  
Details given in this document are believed to be correct at the time of publication.

**Wording of the H-statements in section 2 and 3**

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.

**Classification according to Regulation (EC) No 1272/2008 as amended.**

Flam. Gas 1, H220  
Press. Gas Liq. Gas, H280

**Other information:**

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. ASHRAE: A2L

**Last revised date:**  
**Disclaimer:**

23.03.2020  
This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



**SAFETY DATA SHEET**  
**Difluoromethane (R32)**

Issue Date: 16.01.2013  
Last revised date: 23.03.2020

Version: 1.2

SDS No.: 000010021734  
15/15