



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
1/41

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Hydrogen chloride, anhydrous

Other Name: Hydrogen chloride 2.0; Hydrogen chloride 2.8; Hydrogen chloride 3.0; Hydrogen chloride 4.5 Scientific; Hydrogen chloride 5.0; Hydrogen chloride 5.5

Additional identification

Chemical name: Hydrogen chloride
Chemical formula: HCl
INDEX No. 017-002-00-2
CAS-No. 7647-01-0
EC No. 231-595-7
REACH Registration No. 01-2119484862-27

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Use for electronic component manufacture.
Use gas as catalyst regenerator.
Use of gas to manufacture pharmaceutical products.
Using gas alone or in mixtures for the calibration of analysis equipment.
Using gas as feedstock in chemical processes.
Using gas for metal treatment.
Formulation of mixtures with gas in pressure receptacles.
Intermediate

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Oy Linde Gas Ab
Itsehallintokuja 6
FIN-02600 ESPOO Finland

Telephone: +358 10 2421

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: Poison Information Center: open 24 hours a day, tel. 09 471 977

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
2/41

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.
----------------------	---------------	---

Health Hazards

Acute toxicity (Inhalation - gas)	Category 3	H331: Toxic if inhaled.
Skin corrosion	Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage	Category 1	H318: Causes serious eye damage.

2.2 Label Elements

Contains: Hydrogen chloride



Signal Word: Danger

Hazard Statement(s):
H280: Contains gas under pressure; may explode if heated.
H331: Toxic if inhaled.
H314: Causes severe skin burns and eye damage.

Precautionary Statements

General: None.

Prevention:
P260: Do not breathe gas/vapors.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:
P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Storage:
P403: Store in a well-ventilated place.
P405: Store locked up.

Disposal: None.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
3/41

Supplemental information

EUH071: Corrosive to the respiratory tract.

2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name: Hydrogen chloride
INDEX No.: 017-002-00-2
CAS-No.: 7647-01-0
EC No.: 231-595-7
REACH Registration No.: 01-2119484862-27
Purity: 100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

Trade name: -

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Hydrogen chloride	HCl	100%	7647-01-0	01-2119484862-27	-	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SECTION 4: First aid measures

General:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
4/41

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: None that are more toxic than the product itself.

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
5/41

**Special protective equipment
for fire-fighters:**

Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

**6.1 Personal precautions,
protective equipment and
emergency procedures:**

Evacuate area. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

**6.3 Methods and material for
containment and cleaning up:**

Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections:

Refer to sections 8 and 13.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
6/41

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
7/41

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Hydrogen chloride	TWA	5 ppm 8 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU (12 2009)
	STEL	10 ppm 15 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU (12 2009)
	HTP 15MIN	5 ppm 7,6 mg/m ³	Finland. Workplace Exposure Limits (2009)

DNEL-Values

Critical component	Type	Value	Remarks
Hydrogen chloride	Workers - Inhalation, Local, long-term	8 mg/m ³	respiratory tract irritation
	Workers - Eyes, Local effect		Medium hazard (no threshold derived)
	Workers - Inhalation, Local, short-term	15 mg/m ³	respiratory tract irritation

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
8/41

Individual protection measures, such as personal protective equipment

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
Hand Protection: Guideline: EN 388 Protective gloves against mechanical risks.
Additional Information: Wear working gloves while handling containers
Guideline: EN 374-1 /2/3 Protective gloves against chemicals and micro-organisms.
Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Material: Chloroprene rubber.
Break-through time: > 480 min
Glove thickness: 0,5 mm
- Body protection:** Keep suitable chemically resistant protective clothing readily available for emergency use.
Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
- Other:** Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
9/41

Respiratory Protection:	<p>Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.</p> <p>Material: Filter E</p> <p>Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.</p> <p>Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.</p> <p>Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.</p>
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless to slight yellow
Odor:	Pungent
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	If dissolved in water pH-value will be affected.
Melting Point:	-114,22 °C Other, Not specified
Boiling Point:	-85 °C
Sublimation Point:	Not applicable.
Critical Temp. (°C):	51,4 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	Not applicable.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
10/41

Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	4.260 kPa (20 °C)
Vapor density (air=1):	1,3
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	720 g/l
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	When heated to decomp, emits toxic fumes of hydrogen chloride.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

9.2 Other information:	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Molecular weight:	36,46 g/mol (HCl)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	No reactivity hazard other than the effects described in sub-section below.
10.4 Conditions to avoid:	Avoid moisture in the installation.
10.5 Incompatible Materials:	Moisture. For material compatibility see latest version of ISO-11114. Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas. With water causes rapid corrosion of some metals. May react violently with alkalis.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
11/41

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

**Acute toxicity - Oral
Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal
Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation
Product**

Toxic if inhaled.

Hydrogen chloride

LC 50 (Rat, 4 h): 1405 ppm

LC 50 (Rat, 1 h): 2810 ppm

Remarks: Delayed fatal pulmonary oedema possible.

**Repeated dose toxicity
Hydrogen chloride**

NOAEL (Rat(Female, Male), Inhalation, 4 - 91 d): 10 ppm(m) Inhalation
Experimental result, Key study

**Skin Corrosion/Irritation
Product**

Causes severe burns.

**Serious Eye Damage/Eye Irritation
Product**

Causes serious eye damage.

Hydrogen chloride

in vivo (Rabbit, 1 hrs): Category 1EU

**Respiratory or Skin Sensitization
Product**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity
Product**

Based on available data, the classification criteria are not met.

**Carcinogenicity
Product**

Based on available data, the classification criteria are not met.

Reproductive toxicity



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
12/41

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Hydrogen chloride Severe corrosion to the respiratory tract at high concentrations.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

Acute toxicity - Fish

Hydrogen chloride EC 50 (Fish, 96 h): 3,25 - 3,5 mg/l

Acute toxicity - Aquatic Invertebrates

Hydrogen chloride EC 50 (Water flea (Daphnia magna), 48 h): 4,92 mg/l

Toxicity to Aquatic Plants

Hydrogen chloride EC 50 (Alga, 72 h): 4,7 mg/l

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water pollution.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
13/41

12.5 Results of PBT and vPvB assessment

Product Not classified as PBT or vPvB.

12.6 Other adverse effects:

Other Ecological Information

May cause pH changes in aqueous ecological systems.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Must not be discharged to atmosphere. Consult supplier for specific recommendations.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information

ADR

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name:	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
Hazard No. (ADR):	268
Tunnel restriction code:	(C/D)
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–



SAFETY DATA SHEET **Hydrogen chloride, anhydrous**

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
14/41

RID

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

IMDG

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name:	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2.3
Label(s):	2.3, 8
EmS No.:	F-C, S-U
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

IATA

14.1 UN Number:	UN 1050
14.2 Proper Shipping Name:	Hydrogen chloride, anhydrous
14.3 Transport Hazard Class(es):	
Class:	2.3
Label(s):	–
14.4 Packing Group:	–
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–
Other information	
Passenger and cargo aircraft:	Forbidden.
Cargo aircraft only:	Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
15/41

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Chemical	CAS-No.	Lower-tier Requirements	Upper-tier Requirements
Hydrogen chloride	7647-01-0	25.000 kg	250.000 kg

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen chloride	7647-01-0	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: CSA has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
16/41

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Acute Tox. 3, H331
Skin Corr. 1A, H314
Eye Dam. 1, H318
Press. Gas Liq. Gas, H280



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
17/41

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

06.05.2020

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
18/41

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1.	Industrial use, Formulation & (re)packing of substances and mixtures
Exposure Scenario 2.	Industrial use, Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.
Exposure Scenario 3.	Industrial use, Using gas for metal treatment.
Exposure Scenario 4.	Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

Exposure Scenario 1.

Exposure Scenario worker

1.Industrial use, Formulation & (re)packing of substances and mixtures

List of use descriptors	
Sector(s) of use	
Product categories [PC]:	
Name of contributing environmental scenario and corresponding ERC	Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.: ERC2: Formulation into mixture
Contributing Scenarios	Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

2.1.Contributing exposure scenario controlling environmental exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Product characteristics



SAFETY DATA SHEET **Hydrogen chloride, anhydrous**

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
19/41

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
20/41

Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
21/41

2.2. Contributing exposure scenario controlling worker exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	$\geq 20\text{ }^{\circ}\text{C}$
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	$\leq 8\text{ h}$	5 days per week	PROC1
Hours per shift	$\leq 4\text{ h}$	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
22/41

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
---------------------	-----------------	--------------	---------------	---------



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
23/41

				See section 8 of the safety data sheet (Personal protection equipment)
--	--	--	--	--

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

ERC2:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Water				

Health:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation	0,03 mg/m ³	0,002		none

PROC1:

inhalative, long-term, local	Indoor use, without local exhaust ventilation
------------------------------	---

PROC1:

dermal, short-term, systemic, (acute)	
---------------------------------------	--

PROC1:

dermal, long-term, systemic	
-----------------------------	--

PROC8b:

SDS_FI - 000010021725



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
24/41

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation
PROC8b:	
inhalative, long-term, local	Indoor use, with local exhaust ventilation
PROC8b:	
dermal, short-term, systemic, (acute)	
PROC8b:	
dermal, long-term, systemic	

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 2.

Exposure Scenario worker

1. Industrial use, Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.

List of use descriptors	
Sector(s) of use	SU9: Manufacture of fine chemicals
Product categories [PC]:	PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Using gas as feedstock in chemical processes.:</u> ERC6a: Use of intermediate
---	---

Contributing Scenarios	<u>Using gas as feedstock in chemical processes.:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
25/41

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation.



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
 26/41

	Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
27/41

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1
Hours per shift	<= 4 h	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)

SDS_FI - 000010021725



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
28/41

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation	dermal exposure	eye exposure	oral exposure	Remarks
------------	-----------------	--------------	---------------	---------



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
29/41

exposure				
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.:

ERC6a:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Water				

Health:

Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation	0,03 mg/m ³	0,002		none

PROC1:

inhalative, long-term, local	Indoor use, without local exhaust ventilation
------------------------------	---

PROC1:

dermal, short-term, systemic, (acute)	
---------------------------------------	--



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
30/41

PROC1:

dermal, long-term, systemic	
-----------------------------	--

PROC8b:

inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation
--	--

PROC8b:

inhalative, long-term, local	Indoor use, with local exhaust ventilation
------------------------------	--

PROC8b:

dermal, short-term, systemic, (acute)	
---------------------------------------	--

PROC8b:

dermal, long-term, systemic	
-----------------------------	--

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 3.

Exposure Scenario worker

1. Industrial use, Using gas for metal treatment.

List of use descriptors	
Sector(s) of use	SU14: Manufacture of basic metals, including alloys SU15: Manufacture of fabricated metal products, except machinery and equipment
Product categories [PC]:	PC14: Metal surface treatment products
Name of contributing environmental scenario and corresponding ERC	<u>Using gas for metal treatment.:</u> ERC6a: Use of intermediate ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
Contributing Scenarios	<u>Using gas for metal treatment.:</u> PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature



SAFETY DATA SHEET Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
31/41

--	--

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas for metal treatment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
-----	---



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
32/41

Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
33/41

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas for metal treatment.

Process Categories:	PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
-------------------------------	---------------------------

Vapour pressure:	4260 kPa
------------------	----------

Process temperature:	>= 20 °C
----------------------	----------

Remarks	not relevant
---------	--------------

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
34/41

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
Local exhaust ventilation				Manufacturing and processing of minerals and/or metals at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

SDS_FI - 000010021725



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
35/41

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas for metal treatment.:

ERC6a, ERC6b:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Water				

Health:

Using gas for metal treatment.:

PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC22:

inhalative, long-term, local	Indoor use, with local exhaust ventilation
------------------------------	--

PROC22:

dermal, short-term, systemic, (acute)	
---------------------------------------	--

PROC22:

dermal, long-term, systemic	
-----------------------------	--

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
36/41

Exposure Scenario 4.

Exposure Scenario worker

1. Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

List of use descriptors	
Sector(s) of use	SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals
Name of contributing environmental scenario and corresponding ERC	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
Contributing Scenarios	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> PROC15: Use as laboratory reagent

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
37/41

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
38/41

Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.
----------	---

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Process Categories:	PROC15: Use as laboratory reagent
---------------------	-----------------------------------

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	$\geq 20\text{ }^{\circ}\text{C}$
Remarks	not relevant

Amounts used



SAFETY DATA SHEET

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
39/41

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Use as laboratory reagent
Local exhaust ventilation				Use as laboratory reagent

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
---------------------	-----------------	--------------	---------------	---------



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
40/41

				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas alone or in mixtures for the calibration of analysis equipment.:

ERC8b:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Water				

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

PROC15:

Route of Exposure	Specific	Exposure	RCR	Method	Remarks
-------------------	----------	----------	-----	--------	---------



SAFETY DATA SHEET
Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 06.05.2020

Version: 3.0

SDS No.: 000010021725
41/41

	condition	level			
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC15:

inhalative, long-term, local	Indoor use, with local exhaust ventilation
------------------------------	--

PROC15:

dermal, short-term, systemic, (acute)	
---------------------------------------	--

PROC15:

dermal, long-term, systemic	
-----------------------------	--

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>