

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 1/29

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

**Product name:** Methane, compressed

**Trade name:** Methane 2.5 Chemical, Methane 3.5 Instrument, Methane 4.5 Detector,

Methane 5.5 Scientific

Other Name: G20 (EN 437)

Additional identification

Chemical name:MethaneChemical formula:CH4

INDEX No. 601-001-00-4 CAS-No. 74-82-8 EC No. 200-812-7

**REACH Registration No.** 01-2119474442-39

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Industrial and professional. Perform risk assessment prior to use.

Transfilling gas or liquid, Use as a fuel Use as an Intermediate (transported, on-site isolated). Use for electronic component manufacture. Using gas alone

or in mixtures for the calibration of analysis equipment. Using gas as

feedstock in chemical processes.

**Uses advised against** Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Oy Linde Gas Ab Telephone: +358 10 2421

Itsehallintokuja 6

FIN-02600 ESPOO Finland

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: Poison Information Center: open 24 hours a day, tel. 09 471 977

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

SDS\_FI - 000010021692



## **SAFETY DATA SHEET** Methane, compressed

Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

2/29

Flammable gas Category 1 H220: Extremely flammable gas.

Gases under pressure Compressed gas H280: Contains gas under pressure; may explode if

heated.

#### 2.2 Label Elements



Signal Word: Danger

Hazard Statement(s): H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

**Precautionary Statements** 

General None.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: In case of leakage, eliminate all ignition sources.

P403: Store in a well-ventilated place. Storage:

Disposal None.

2.3 Other hazards None.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 3/29

## SECTION 3: Composition/information on ingredients

#### 3.1 Substances

 Chemical name
 Methane

 INDEX No.:
 601-001-00-4

 CAS-No.:
 74-82-8

 EC No.:
 200-812-7

**REACH Registration No.:** 01-2119474442-39

Purity: 100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other

documentation should be consulted.

**Trade name:** Methane 2.5 Chemical, Methane 3.5 Instrument, Methane 4.5 Detector, Methane

5.5 Scientific

Chemical name	Chemical formula	Concentration		REACH Registration No.	M-Factor:	Notes
Methane	CH4	100%	74-82-8	01- 2119474442-	-	#
				39		

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

PBT: persistent, bioaccumulative and toxic substance.

#### SECTION 4: First aid measures

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Adverse effects not expected from this product.

**Skin Contact:** Adverse effects not expected from this product.

**Ingestion:** Ingestion is not considered a potential route of exposure.

<sup># #</sup> This substance has workplace exposure limit(s).

vPvB: very persistent and very bioaccumulative substance.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 4/29

4.2 Most important symptoms and

effects, both acute and

delayed:

Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

### SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water. Dry powder. Foam.

Unsuitable extinguishing

media:

Carbon Dioxide.

5.2 Special hazards arising from the

substance or mixture:

Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting

procedures:

In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the

fire. Isolate the source of the fire or let it burn out.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.



# **SAFETY DATA SHEET** Methane, compressed

SDS No.: 000010021692 Issue Date: 16.01.2013 Version: 3.0 Last revised date: 12.05.2020

5/29

## SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements,

testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections: Refer to sections 8 and 13.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692 Last revised date: 12.05.2020

6/29

### SECTION 7: Handling and storage:

#### 7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 7/29

7.3 Specific end use(s): None.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Methane	HTP 8H	1.000 ppm	Finland. Workplace Exposure Limits (07 2018)

#### 8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

#### Individual protection measures, such as personal protective equipment

**General information:** A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product. The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

**Eye/face protection:** Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

**Hand Protection:** Guideline: EN 388 Protective gloves against mechanical risks.

Additional Information: Wear working gloves while handling containers



Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 8/29

**Body protection:** Wear fire resistant or flame retardant clothing.

Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.

**Other:** Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

**Respiratory Protection:** Not required.

**Thermal hazards:** No precautionary measures are necessary.

**Hygiene measures:** Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13 of the SDS.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state: Gas

Form: Compressed gas
Color: Colorless

Odor: Odorless

Odor Threshold: Odor threshold is subjective and is inadequate to warn of over

exposure.

pH: Not applicable.

Melting Point: -182,47 °C Experimental result, Key study

Boiling Point: -161,48 °C (1.013 hPa) Experimental result, Key study

Sublimation Point: Not applicable. Critical Temp. (°C): -82,0 °C

**Flash Point:**Not applicable to gases and gas mixtures. **Evaporation Rate:**Not applicable to gases and gas mixtures.

Flammability (solid, gas): Flammable Gas

Flammability Limit - Upper (%): 17 %(V)
Flammability Limit - Lower (%): 4,4 %(V)

Vapor pressure: No reliable data available.

Vapor density (air=1): 0,6

Relative density: 0,42 (25 °C)

Solubility(ies)

SDS\_FI - 000010021692



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 9/29

Solubility in Water: 22 mg/l (25 °C)

Partition coefficient (n-octanol/water): 1,09

**Autoignition Temperature:** 537 °C Experimental result, Key study

**Decomposition Temperature:** Not known.

Viscosity

Kinematic viscosity:No data available.Dynamic viscosity:0,011 mPa.s (27 °C)Explosive properties:Not applicable.Oxidizing properties:Not applicable.

**9.2 Other information:** None.

Molecular weight: 16,04 g/mol (CH4)

Minimum ignition energy: 0,21 mJ

## SECTION 10: Stability and reactivity

**10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.

**10.2 Chemical Stability:** Stable under normal conditions.

10.3 Possibility of hazardous

reactions:

Can form a potentially explosive atmosphere in air. May react violently with

oxidants.

**10.4 Conditions to avoid:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

**10.5 Incompatible Materials:** Air and oxidizers. For material compatibility see latest version of ISO-11114.

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## SECTION 11: Toxicological information

**General information:** None.

#### 11.1 Information on toxicological effects

Acute toxicity - Oral

**Product** Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 10/29

Acute toxicity - Dermal

**Product** Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

**Product** Based on available data, the classification criteria are not met.

Methane LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key

study

Repeated dose toxicity

Methane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation

Read-across based on grouping of substances (category approach), Key study

Skin Corrosion/Irritation

**Product** Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation

**Product** Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization

**Product** Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

**Product** Based on available data, the classification criteria are not met.

In vitro

Methane Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome

Aberration Test)): Negative.

In vivo

Methane Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Carcinogenicity

**Product** Based on available data, the classification criteria are not met.

Reproductive toxicity

**Product** Based on available data, the classification criteria are not met.



Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 11/29

Reproductive toxicity (Fertility)

Methane Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity

Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity

Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 3.000 ppm

Developmental toxicity (Teratogenicity)

Methane Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study

with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Specific Target Organ Toxicity - Single Exposure

**Product** Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

**Product** Based on available data, the classification criteria are not met.

Aspiration Hazard

**Product** Not applicable to gases and gas mixtures..

#### SECTION 12: Ecological information

#### 12.1 Toxicity

Acute toxicity

**Product** No ecological damage caused by this product.

Acute toxicity - Fish

Methane LC 50 (Various, 96 h): 49,9 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates

Methane LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study

Toxicity to microorganisms

Methane EC 50 (Alga, 96 h): 8,57 mg/l

12.2 Persistence and Degradability

**Product** Not applicable to gases and gas mixtures...



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 12/29

Biodegradation

Methane 50 % (3,19 d) Detected in water. QSAR, Weight of Evidence study

12.3 Bioaccumulative potential

**Product** The subject product is expected to biodegrade and is not expected to persist for

long periods in an aquatic environment.

12.4 Mobility in soil

**Product** Because of its high volatility, the product is unlikely to cause ground or water

pollution.

12.5 Results of PBT and vPvB

 $\underset{\cdot}{\text{assessment}}$ 

**Product** Not classified as PBT or vPvB.

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 25

Contains greenhouse gas(es). When discharged in large quantities may contribute

to the greenhouse effect.

Methane EU. Non-Fluorinated Substance GWPs (Annex IV), Regulation 517/2014/EU on

<u>fluorinated greenhouse gases</u> - Global warming potential: 25

#### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**General information:** Do not discharge into any place where its accumulation could be dangerous.

Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared

through a suitable burner with flash back arrestor.

**Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

**European Waste Codes** 

Container: 16 05 04\*: Gases in pressure containers (including halons) containing

dangerous substances.



# **SAFETY DATA SHEET** Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692 Last revised date: 12.05.2020

13/29

## SECTION 14: Transport information

ADR

14.1 UN Number: UN 1971

14.2 UN Proper Shipping Name: METHANE, COMPRESSED

14.3 Transport Hazard Class(es)

2 Class: Label(s): 2.1 Hazard No. (ADR): 23 Tunnel restriction code: (B/D)

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

RID

14.1 UN Number: UN 1971

14.2 UN Proper Shipping Name METHANE, COMPRESSED

14.3 Transport Hazard Class(es)

Class: 2 Label(s): 2.1 14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

**IMDG** 

14.1 UN Number: UN 1971

14.2 UN Proper Shipping Name: METHANE, COMPRESSED

14.3 Transport Hazard Class(es)

Class: 2.1 Label(s): 2.1 EmS No.: F-D, S-U

14.4 Packing Group:

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:



Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 14/29

IATA

14.1 UN Number: UN 1971

14.2 Proper Shipping Name: Methane, compressed

14.3 Transport Hazard Class(es):

Class: 2.1 Label(s): 2.1 14.4 Packing Group: -

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Forbidden. Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from

the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure

adequate air ventilation.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

**EU Regulations** 

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	100%

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Classification	Lower-tier	Upper-tier
	Requirements	Requirements
P2: Flammable gases,	10 t	50 t
Category 1 or 2		

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692 Last revised date: 12.05.2020

15/29

Chemical name	CAS-No.	Concentration
Methane	74-82-8	100%

#### **National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

**15.2 Chemical safety assessment:** CSA has been carried out.

## SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling

quide", as amended.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and

oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/). The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental

Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 16/29

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

**Training information:** Users of breathing apparatus must be trained. Ensure operators understand the

flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1, H220

Press. Gas Compr. Gas, H280

**Other information:**Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no

liability for injury or damage resulting from its use can be accepted.

Last revised date: 12.05.2020

**Disclaimer:** This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.



SDS No.: 000010021692 Issue Date: 16.01.2013 Version: 3.0 Last revised date: 12.05.2020

17/29

# Annex to the extended Safety Data Sheet (eSDS)

Content

Industrial:, Formulation of mixtures with gas in pressure receptacles, Exposure Scenario 1.

Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, on-site isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.

Exposure Scenario 2. Professional:, Use as a fuel, Using gas alone or in mixtures for the calibration of

analysis equipment., Laboratory activities

Exposure Scenario 1.

Exposure Scenario worker

1.Industrial:, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, on-site isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.

List of use descriptors		
Sector(s) of use	SU9: Manufacture of fine chemicals	
	SU16: Manufacture of computer, electronic and optical products, electrical equipment	
	SU24: Scientific research and development	
Product categories [PC]:	PC13: Fuels	
	PC21: Laboratory chemicals	
	PC33: Semiconductors	

Name of contributing environmental scenario and corresponding ERC	Industrial use: ERC2: Formulation into mixture
	ERC6a: Use of intermediate
	ERC7: Use of functional fluid at industrial site



Version: 3.0 Issue Date: 16.01.2013 SDS No.: 000010021692 Last revised date: 12.05.2020

18/29

batch processes with occasional controlled exposure or processes with equivalent containment condition  PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities  PROC15: Use as laboratory reagent  PROC16: Use of fuels	Contributing Scenarios	with equivalent containment condition  PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities  PROC15: Use as laboratory reagent
--	------------------------	---

2.1.Contributing exposure scenario controlling environmental exposure for: Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, onsite isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.

Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Thysical form of the product	See section 7 of the 303.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,011 mPa.s (27 °C)
Amounts used	
Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
Frequency and duration of use	
Batch process:	260 Emission days
Continuous process:	260 Emission days

## Environment factors not influenced by risk management



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

19/29

## Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

#### Risk management measures (RMM)

#### Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 98 %.
Soil	not relevant
Water	not relevant
Sediment:	not relevant
Remarks:	not relevant

## Organisational measures to prevent/limit release from site:

none

#### Conditions and measures related to sewage treatment plant

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

## Conditions and measures related to external treatment of waste for disposal

#### Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

20/29

	should comply with applicable local and/or national regulations.
--	--

## Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

#### Additional good practice advice beyond the REACH Chemical Safety Report

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, on-site isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15: Use as laboratory reagent
	PROC16: Use of fuels

#### Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	not relevant
Process temperature:	not relevant
Remarks	not relevant

#### Amounts used



# **SAFETY DATA SHEET** Methane, compressed

Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

21/29

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.

## Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Covers daily exposures up to 8		5 days per week	PROC1, PROC3, PROC8b, PROC15, PROC16
hours			

#### Human factors not influenced by risk management

This information is not available.

#### Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

## Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

### Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
Local exhaust ventilation				Manufacture or formulation in the chemical industry in



# **SAFETY DATA SHEET** Methane, compressed

Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

22/29

		closed batch processes with occasional controlled exposure or processes with equivalent containment condition
Provide a basic standard of general ventilation (1 to 3 air changes per hour).		Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation		Transfer of substance or mixture (charging and discharging) at dedicated facilities
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).		Use as laboratory reagent
Local exhaust ventilation		Use as laboratory reagent
Provide a basic standard of general ventilation (1 to 3 air changes per hour).		Use of fuels

## Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS. Ensure operatives are trained to minimise exposures. Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

## Conditions and measures related to personal protection, hygiene and health evaluation



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

23/29

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

#### Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

#### 3. Exposure estimation

#### **Environment:**

Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, on-site isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.:

ERC2, ERC6a, ERC7:

Compartment	PEC	RCR	Method	Remarks
Air		<1		Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

#### Health:

Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities, Use as feedstock in chemical processes, use as an Intermediate (transported, on-site isolated)., Manufacture of fine chemicals, Use for electronic component manufacture.:

PROC1, PROC3, PROC8b, PROC15, PROC16:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalation exposure	Indoor/Outd oor use.		<1		As no toxicological hazard was identified no human-related (worker/consumer) exposure assessment and risk characterization was performed.



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

24/29

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra

#### Exposure Scenario 2.

## Exposure Scenario worker

1. Professional:, Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities

List of use descriptors	
Sector(s) of use	SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals
Name of contributing onvironmental sconario	Professional use.

Name of contributing environmental scenario and corresponding ERC	Professional use: ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)  ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)  ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)  ERC9a: Widespread use of functional fluid (indoor)  ERC9b: Widespread use of functional fluid (outdoor)
	ERC9b: Widespread use of functional fluid (outdoor)

Contributing Scenarios	Professional use: PROC15: Use as laboratory reagent
	PROC16: Use of fuels

2.1.Contributing exposure scenario controlling environmental exposure for: Professional use, Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

25/29

Physical form of the product	See section 9 of the SDS.	
F.,		
Viscosity:		
Kinematic viscosity:	No data available.	
Dynamic viscosity:	0,011 mPa.s (27 °C)	
Amounts used		
Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release	
Frequency and duration of use		
Batch process:	260 Emission days	
Continuous process:	260 Emission days	
Other given operational conditions affecting environmental exposure		
Other relevant operational conditions	not relevant	
other relevant operational conditions	Hotreievant	
Risk management measures (RMM)		
Technical conditions and measures at process	s level (source) to prevent release	
See section 8 of the safety data sheet (Environmental exposure controls).		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil		
Air	Handle substance within a closed system. Effectiveness: 98 %.	
Soil	not relevant	
Water	not relevant	
Sediment:	not relevant	
Remarks:	not relevant	

Organisational measures to prevent/limit release from site:



SDS No.: 000010021692 Issue Date: 16.01.2013 Version: 3.0 Last revised date: 12.05.2020

26/29

none

#### Conditions and measures related to sewage treatment plant

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

#### Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

## Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

### Additional good practice advice beyond the REACH Chemical Safety Report

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Professional use, Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities

Process Categories:	PROC15: Use as laboratory reagent	
	PROC16: Use of fuels	

#### Product characteristics



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

27/29

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 % (unless stated differently).
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	not relevant
Process temperature:	not relevant
Remarks	not relevant

#### Amounts used

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.

#### Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Covers daily exposures up to 8		5 days per week	PROC15, PROC16
hours			

#### Human factors not influenced by risk management

This information is not available.

### Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.

#### Risk management measures (RMM)

#### Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

## Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of controlled ventilation (10 to 15				Use as laboratory reagent



Version: 3.0 SDS No.: 000010021692 Issue Date: 16.01.2013 Last revised date: 12.05.2020

28/29

air changes per hour).		
Local exhaust ventilation		Use as laboratory reagent
Provide a basic standard of general ventilation (1 to 3 air changes per hour).		Use of fuels

### Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS. Ensure operatives are trained to minimise exposures. Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

## Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

## Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

#### 3. Exposure estimation

Environment:

Professional use, Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities:

ERC8a, ERC8b, ERC8e, ERC9a, ERC9b:



# SAFETY DATA SHEET Methane, compressed

Issue Date: 16.01.2013 Version: 3.0 SDS No.: 000010021692

Last revised date: 12.05.2020 29/29

Compartment	PEC	RCR	Method	Remarks
Air		< 1		Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

#### Health:

Professional use, Use as a fuel, Using gas alone or in mixtures for the calibration of analysis equipment., Laboratory activities:

#### PROC15, PROC16:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalation exposure	Indoor use		<1		As no toxicological hazard was identified no human-related (worker/consumer) exposure assessment and risk characterization was performed.

## 4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra