



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
1/15

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name:	Nitrogen Dioxide
Trade name:	Nitrogen dioxide 2.0
Other Name:	Dinitrogen tetroxide, Nitrogen(IV)-oxide, Nitrogen oxides
<b>Additional identification</b>	
Chemical name:	Nitrogen dioxide
Chemical formula:	NO <sub>2</sub>
INDEX No.	007-002-00-0
CAS-No.	10102-44-0
EC No.	233-272-6
REACH Registration No.	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:	Industrial and professional. Perform risk assessment prior to use.
Uses advised against	Consumer use.

### 1.3 Details of the supplier of the safety data sheet

<b>Supplier</b>	<b>Telephone:</b> +358 10 2421
Oy Linde Gas Ab	
Itsehallintokuja 6	
FIN-02600 ESPOO Finland	
<b>E-mail:</b> sds.ren@linde.com	

**1.4 Emergency telephone number:** Poison Information Center: open 24 hours a day, tel. 09 471 977

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

#### Physical Hazards

Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.
Oxidizing gases	Category 1	H270: May cause or intensify fire; oxidizer.

#### Health Hazards

Acute toxicity (Inhalation - gas)	Category 1	H330: Fatal if inhaled.
-----------------------------------	------------	-------------------------



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
2/15

Skin corrosion  
Serious eye damage

Category 1B  
Category 1

H314: Causes severe skin burns and eye damage.  
H318: Causes serious eye damage.

## 2.2 Label Elements

Contains:

Nitrogen dioxide



Signal Words:

Danger

Hazard Statement(s):

H270: May cause or intensify fire; oxidizer.  
H280: Contains gas under pressure; may explode if heated.  
H330: Fatal if inhaled.  
H314: Causes severe skin burns and eye damage.

## Precautionary Statements

Prevention:

P220: Keep away from clothing and other combustible materials.  
P244: Keep valves and fittings free from oil and grease.  
P260: Do not breathe gas/vapors.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.  
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.  
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.  
P370+P376: In case of fire: Stop leak if safe to do so.

Storage:

P403: Store in a well-ventilated place.  
P405: Store locked up.

Disposal:

None.

## Supplemental label information

EUH071: Corrosive to the respiratory tract.

## 2.3 Other hazards:

Contact with evaporating liquid may cause frostbite or freezing of skin.



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
3/15

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Chemical name	Nitrogen dioxide
INDEX No.:	007-002-00-0
CAS-No.:	10102-44-0
EC No.:	233-272-6
REACH Registration No.:	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.
Purity:	100% The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	Nitrogen dioxide 2.0

## SECTION 4: First aid measures

**General:** Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

### 4.1 Description of first aid measures

<b>Inhalation:</b>	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
<b>Eye contact:</b>	Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
<b>Skin Contact:</b>	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.
<b>Ingestion:</b>	Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled. May result in pulmonary oedema

### 4.3 Indication of any immediate medical attention and special treatment needed

**Hazards:** Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled. May result in pulmonary oedema



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
4/15

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

#### SECTION 5: Firefighting measures

**General Fire Hazards:** Heat may cause the containers to explode.

##### 5.1 Extinguishing media

**Suitable extinguishing media:** Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.

**Unsuitable extinguishing media:** None.

**5.2 Special hazards arising from the substance or mixture:** Fire or excessive heat may produce hazardous decomposition products. Fire or excessive heat may produce hazardous decomposition products.

**Hazardous Combustion Products:** If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Nitrogen monoxide

##### 5.3 Advice for firefighters

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

**Special protective equipment for fire-fighters:** Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus. Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

#### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. In case of leakage, eliminate all ignition sources. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
5/15

- 6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.
- 6.4 Reference to other sections:** Refer to sections 8 and 13.

## SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep equipment free from oil and grease. Open valve slowly to avoid pressure shock. Use only oxygen approved lubricants and sealants. Use only with equipment cleaned for oxygen service and rated for the pressure. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
- 7.2 Conditions for safe storage, including any incompatibilities:** Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material. Avoid asphalted locations for storage, transfer and use (ignition risk if spilt). Segregate from flammable gases and other flammable materials being stored.



## SAFETY DATA SHEET

## Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
6/15

7.3 Specific end use(s): None.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control Parameters

## Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Nitrogen dioxide	HTP 8H	0,5 ppm 0,96 mg/m <sup>3</sup>	Finland. Workplace Exposure Limits (2018)
	HTP 15MIN	1 ppm 1,9 mg/m <sup>3</sup>	Finland. Workplace Exposure Limits (2018)
	TWA	0,5 ppm 0,96 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU (02 2017)
	STEL	1 ppm 1,91 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU (02 2017)

## 8.2 Exposure controls

## Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of oxidizing gases may be released. Avoid oxygen rich (>23,5%) atmospheres. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.

## Individual protection measures, such as personal protective equipment

## General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
7/15

<b>Eye/face protection:</b>	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
<b>Skin protection</b>	
<b>Hand Protection:</b>	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks. Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms. Material: Polyvinyl chloride (PVC). Break-through time: > 60 min
<b>Body protection:</b>	No special precautions.
<b>Other:</b>	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
<b>Respiratory Protection:</b>	Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
<b>Thermal hazards:</b>	No precautionary measures are necessary.
<b>Hygiene measures:</b>	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
<b>Environmental exposure controls:</b>	For waste disposal, see section 13 of the SDS.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state:</b>	Gas
<b>Form:</b>	Liquefied gas
<b>Color:</b>	Brown
<b>Odor:</b>	Pungent acrid odor
<b>Odor Threshold:</b>	Odor threshold is subjective and is inadequate to warn of over exposure.
<b>pH:</b>	Not applicable.
<b>Melting Point:</b>	No data available.





## SAFETY DATA SHEET

## Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
8/15

Boiling Point:	21,1 °C
Sublimation Point:	-11,2 °C
Critical Temp. (°C):	158,0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	96 kPa (20 °C)
Vapor density (air=1):	2,8
Relative density:	1,448 (20 °C)
Solubility(ies)	
Solubility in Water:	Completely Soluble
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	When heated to decomp, emits toxic fumes of nitroxides.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,42 mPa.s (26,8 °C)
Explosive properties:	Not applicable.
Oxidizing properties:	Oxidizing

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight: 46,01 g/mol (NO<sub>2</sub>)

**SECTION 10: Stability and reactivity**

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Violently oxidises organic material. May react violently with combustible materials. May react violently with reducing agents. May react violently with alkalis.
10.4 Conditions to avoid:	Avoid moisture in the installation.





## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
9/15

- 10.5 Incompatible Materials:** Moisture. Combustible materials Reducing agents. Keep equipment free from oil and grease. For material compatibility see latest version of ISO-11114. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (>30 bar) oxygen lines and equipment in case of combustion. Reacts with water to form corrosive acids.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

**General information:** None.

### 11.1 Information on toxicological effects

**Acute toxicity - Oral Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation Product** Fatal if inhaled.

Nitrogen dioxide LC 50 (Rat, 1 h): 115 ppm

**Skin Corrosion/Irritation Product** Causes severe burns.

**Serious Eye Damage/Eye Irritation Product** Causes serious eye damage.

**Respiratory or Skin Sensitization Product** Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity Product** Based on available data, the classification criteria are not met.

**Carcinogenicity Product** Based on available data, the classification criteria are not met.

**Reproductive toxicity Product** Based on available data, the classification criteria are not met.



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
10/15

#### Specific Target Organ Toxicity - Single Exposure

**Product** Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity - Repeated Exposure

**Product** Based on available data, the classification criteria are not met.

#### Aspiration Hazard

**Product** Not applicable to gases and gas mixtures..

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Acute toxicity

**Product** No ecological damage caused by this product.

#### Acute toxicity - Fish

Nitrogen dioxide LC 50 (Tench (Tinca tinca), 24 h): 41,2 mg/l (Renewal) Remarks: Mortality

#### Acute toxicity - Aquatic Invertebrates

Nitrogen dioxide LC 50 (Redtail prawn (Penaeus penicillatus), 24 h): 83,34 mg/l (Renewal) Remarks: Mortality

### 12.2 Persistence and Degradability

**Product** Not applicable to gases and gas mixtures..

### 12.3 Bioaccumulative potential

**Product** The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

### 12.4 Mobility in soil

**Product** Because of its high volatility, the product is unlikely to cause ground or water pollution.

### 12.5 Results of PBT and vPvB assessment

**Product** Not classified as PBT or vPvB.

### 12.6 Other adverse effects:

No ecological damage caused by this product.



## SAFETY DATA SHEET

## Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
11/15

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- General information:** Must not be discharged to atmosphere. Consult supplier for specific recommendations.
- Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws. Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.
- European Waste Codes**
- Container:** 16 05 04\*: Gases in pressure containers (including halons) containing dangerous substances.

**SECTION 14: Transport information****ADR**

- 14.1 UN Number: UN 1067  
14.2 UN Proper Shipping Name: NITROGEN DIOXIDE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.3, 5.1, 8  
Hazard No. (ADR): 265  
Tunnel restriction code: (C/D)  
14.4 Packing Group: –  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: –

**RID**

- 14.1 UN Number: UN 1067  
14.2 UN Proper Shipping Name: NITROGEN DIOXIDE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.3, 5.1, 8  
14.4 Packing Group: –  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: –



## SAFETY DATA SHEET

## Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
12/15

## IMDG

14.1 UN Number: UN 1067  
14.2 UN Proper Shipping Name: NITROGEN DIOXIDE  
14.3 Transport Hazard Class(es)  
Class: 2.3  
Label(s): 2.3, 5.1, 8  
EmS No.: F-C, S-W  
14.4 Packing Group: –  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: –

## IATA

14.1 UN Number: UN 1067  
14.2 Proper Shipping Name: Nitrogen dioxide  
14.3 Transport Hazard Class(es):  
Class: 2.3  
Label(s): –  
14.4 Packing Group: –  
14.5 Environmental hazards: Not applicable  
14.6 Special precautions for user: –  
Other information  
Passenger and cargo aircraft: Forbidden.  
Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

## EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Classification	Lower-tier Requirements	Upper-tier Requirements
P4: Oxidising gases, Category	50 t	200 t



## SAFETY DATA SHEET

## Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
13/15

1		
H1: ACUTE TOXIC Category 1, all exposure routes	5 t	20 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Nitrogen dioxide	10102-44-0	100%

## National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Revision Information: Not relevant.



## SAFETY DATA SHEET

### Nitrogen Dioxide

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
14/15

#### Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

- Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
- European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
- European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
- European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.
- International Programme on Chemical Safety (<http://www.inchem.org/>)
- ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
- Matheson Gas Data Book, 7th Edition.
- National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
- The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
- The European Chemical Industry Council (CEFIC) ERICards.
- United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
- Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
- Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

#### Wording of the H-statements in section 2 and 3

H270	May cause or intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

#### Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Liq. Gas, H280  
Ox. Gas 1, H270  
Acute Tox. 1, H330  
Skin Corr. 1B, H314  
Eye Dam. 1, H318

#### Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.



**SAFETY DATA SHEET**

**Nitrogen Dioxide**

Issue Date: 16.01.2013  
Last revised date: 13.04.2020

Version: 1.1

SDS No.: 000010021798  
15/15

**Last revised date:**  
**Disclaimer:**

13.04.2020

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.